



PipeCut 220 Pro Series

- Integrated laser for perfect cutting
- More power through a stronger engine
- Optical display for optimum worker guidance
- Optional saw blade housing with suction connection available

Weight	11,5 kg
Range of use	20 - 220 mm
Max. pipe wall	16 mm steel 35 mm plastics
Suitable for	All materials

Technical data

Voltage / Power	220-240V 1.600W 7,6A
No-load speed	I=1.900, II=2.885 rpm
Ø Blade diameter	165 mm
Mounting bore	62 mm



Scope of delivery
PipeCut Pro Series, Carrying bag, Cermet 165 Saw blade, 4 x pipe supports, operating instructions, hexagon socket 5 mm & 2 mm

PipeCut 280 Pro Series

- Integrated laser for perfect cutting
- Optical display for optimum worker guidance
- Optional saw blade housing with suction connection available

Weight	15,5 kg
Range of use	40 - 280 mm
Max. pipe wall	20 mm steel 45 mm plastics
Suitable for	All materials

Technical data

Voltage / Power	220-240V 2.500W 12A
No-load speed	I=1.900, II=2.885 rpm
Ø Blade diameter	165 mm
Mounting bore	62 mm



Scope of delivery
PipeCut Pro Series, Carrying bag, Cermet 165 Saw blade, 3 pipe supports (1 x double and 2 x single), operating instructions, hexagon socket 5 mm & 2 mm

PipeCut 360 Pro Series

- Integrated laser for perfect cutting
- Optical display for optimum worker guidance
- More powerful motor with overload protection
- Optional saw blade housing with suction connection available

Weight	17,5 kg
Range of use	75 - 360 mm
Max. pipe wall	20 mm steel 50 mm plastics
Suitable for	All materials

Technical data

Voltage / Power	220-240V 2500W 12A
No-load speed	I=1.900, II=2.885 rpm
Ø Blade diameter	165 mm
Mounting bore	62 mm



Scope of delivery
PipeCut Pro Series, Carrying bag, Cermet 165 Saw blade, 3 pipe supports (1 x double and 2 x single), operating instructions, hexagon socket 5 mm & 2 mm

PipeCut 460 Pro Series

- Cutting of thick and large pipes
- Cuts all pipe materials
- Optical display for optimum worker guidance
- Integrated laser for perfect cutting
- Soft start
- Speed control

Weight	18,5 kg
Range of use	100 - 460 mm
Max. pipe wall	20 mm steel 50 mm plastics
Suitable for	All materials

Technical data

Voltage / Power	220-240V 2.500W 12A
No-load speed	I=1.900, II=2.885 rpm
Ø Blade diameter	165 mm
Mounting bore	62 mm



Scope of delivery
PipeCut Pro Series, Carrying bag, Cermet 165 Saw blade, 3 pipe supports (1 x double and 2 x single), operating instructions, hexagon socket 5 mm & 2 mm